

Configuration des serveur DHCP



Sommaire

1. *Configuration des pool sur le serveur Maître*
2. *Configuration des pool sur le serveur Secondaire*

Configuration du serveur Maître

```
failover peer "PPE_DHCP_Failover" {
    primary;
    address 192.168.3.129;
    port 54054;
    peer address 192.168.3.130;
    peer port 54054;
    max-response-delay 3;
    max-unacked-updates 2;
    load balance max seconds 3;
    mclt 1800;
    split 128;
}
log-facility local7;

subnet 10.7.10.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.10.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.10.1 10.7.10.100;
    }
}

subnet 10.7.20.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.20.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.20.1 10.7.20.100
    }
}

subnet 10.7.30.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.30.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.30.1 10.7.30.100;
    }
}
```

```
subnet 10.7.40.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.40.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.40.1 10.7.40.100;
    }
}

subnet 10.7.50.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.50.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.50.1 10.7.50.100;
    }
}

subnet 10.7.60.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.60.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.60.1 10.7.60.100;
    }
}
```

Configuration du serveur Secondaire

```
failover peer "PPE_DHCP_Failover" {
    secondary;
    address 192.168.3.130;
    port 54054;
    peer address 192.168.3.129;
    peer port 54054;
    max-response-delay 3;
    max-unacked-updates 2;
    load balance max seconds 3;
}
log-facility local7;

subnet 10.7.10.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.10.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.10.101 10.7.10.199;
    }
}

subnet 10.7.20.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.20.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.20.101 10.7.20.199
    }
}

subnet 10.7.30.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.30.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.30.101 10.7.30.199;
    }
}

subnet 10.7.40.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.40.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.40.101 10.7.40.199;
    }
}

subnet 10.7.50.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.50.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.50.101 10.7.50.199;
    }
}
```

```
subnet 10.7.60.0 netmask 255.255.255.0 {
    option domain-name-servers 192.168.2.253;
    option domain-name "sio2.lan";
    option routers 10.7.60.254;
    pool {
        failover peer "PPE_DHCP_Failover";
        range 10.7.60.101 10.7.60.199;
    }
}
```